



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of
NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on December 15, 2023.

Toray Advanced Materials Korea Inc.
6F, 7, Magokdong-ro 10-gil
Gangseo-gu, Seoul 07790
Korea, Republic of
82 23 279 7000

Facility: Gyeongsangbuk-do, Republic of Korea

Mechanical Devices

Trade Designation	Size	Water Contact Temp	Water Contact Material
Reverse Osmosis Element ^[1]			
NE4040-40 ^[2]	4" x 40"	CLD 23	MLTPL
NE4040-70 ^[2]	4" x 40"	CLD 23	MLTPL
NE4040-90 ^[2]	4" x 40"	CLD 23	MLTPL
NE8040-40 ^[2]	8" x 40"	CLD 23	MLTPL
NE8040-70 ^[2]	8" x 40"	CLD 23	MLTPL
NE8040-90 ^[2]	8" x 40"	CLD 23	MLTPL
RE16040-BE ^[3]	16" x 40"	CLD 23	MLTPL
RE16040-BLN ^[3]	16" x 40"	CLD 23	MLTPL
RE16040-BLR ^[3]	16" x 40"	CLD 23	MLTPL
RE16040-FE ^[3]	16" x 40"	CLD 23	MLTPL
RE16040-FEn ^[3]	16" x 40"	CLD 23	MLTPL
RE16040-SHF ^[3]	16" x 40"	CLD 23	MLTPL
RE16040-SHN ^[3]	16" x 40"	CLD 23	MLTPL
RE4021-BLF ^[5] [6]	4" x 21"	CLD 23	MLTPL
RE4040-BE ^[5] [6]	4" x 40"	CLD 23	MLTPL
RE4040-BLF ^[2]	4" x 40"	CLD 23	MLTPL
RE4040-BLN ^[2]	4" x 40"	CLD 23	MLTPL
RE4040-BLR ^[2]	4" x 40"	CLD 23	MLTPL
RE4040-CE ^[2] [4]	4" x 40"	CLD 23	MLTPL
RE8040-BE ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-BE34 ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-BE440 ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-BLF ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-BLF440 ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-BLN ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-BLN440 ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-BLR ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-BLR440 ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-BN ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-CE ^[3]	8" x 40"	CLD 23	MLTPL

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



RE8040-FDn ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-FE ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-FEn ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-FEN34	8" x 40"	CLD 23	MLTPL
RE8040-FEn440 ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-FLF ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-FLF34 ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-FLF440 ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-FLR ^[5] [6]	8" x 40"	CLD 23	MLTPL
RE8040-FLR34 ^[2]	8" x 40"	CLD 23	MLTPL
RE8040-FLR440 ^[5] [6]	8" x 40"	CLD 23	MLTPL
RE8040-FN ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-SFR ^[5] [6]	8" x 40"	CLD 23	MLTPL
RE8040-SHF ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-SHF400 ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-SHN ^[3]	8" x 40"	CLD 23	MLTPL
RE8040-SHN400 ^[3]	8" x 40"	CLD 23	MLTPL

[1] Sizes refer to the diameter x length.

[2] Certified for a minimum flow of 8,330 liters per day.

[3] Certified for a minimum permeate flow of 20,000 liters per day.

[4] Elements require a 30 minute pre-service flush.

[5] Elements require a 1 hr pre-service flush.

[6] Certified for the following minimum permeate flow rates (gallons per day)

RE 4021-BLF : 2,220
RE 4040-BE : 2,220
RE 8040-FLR : 9,000
RE 8040-FLR440 : 9,900
RE 8040-SFR : 7,500

NOTE: Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.